

Keystroke™

Point Of Sale

Ithaca Series 90PLUS Printers



PRINTER INFORMATION

Ithaca Model:	93PL
Ithaca Part Number:	SRB-11456-005
Ithaca Serial Number:	HP001975057
Programmer Manual:	Ithaca P/N: 100-7307 Rev G 06/10/97
Receipt Paper:	3.25" Single Ply Ithaca P/N: 100-1667 3.25" Double Ply Ithaca P/N: 98-0558 3.25" Triple Ply Ithaca P/N: 06-0720
Label Stock:	None Supplied, Manual does not reference label stock.
Interface:	Serial 9F-9F, Ithaca Cable P/N 10-2020 (Supplied) or Serial 9F-25F, Ithaca Cable P/N 10-2021
Wiring:	4-(6/1),(6/1)-4,3-2,2-3,5-5,7-8,8-7
Power Supply:	Within printer, regular 100-120VAC

Keystroke POS Setup Information:

RECEIPT PRINTING

Printer Driver:	ITH90RCT.PRD
Com Parameters:	9600,N,8,1,LF
DOS Command:	None
Form Files:	STAR.NVC (Or any STAR*.NVC form)
Cut Command:	If Equipped: 27,118

CASH DRAWER

Drawer Open Codes:	27,120,1 (Not tested)
Drawer Status Codes:	27,119,0 (Not tested) 27,119,1 for drawer#2

CHECK VALIDATION PRINTING (Front, Form must be positioned far Right)

Printer Driver:	ITH90RCT.PRD
Select Rcpt Printing:	27,102 (ITH90RCT.PRD Setup String)
Select Slip Printing:	27,105 (Code 11 On)
Eject Slip	27,107 (Code 12 On)
Form Files:	ITHVALID.NVC (Prints Date, Nvc#, Amount, Form Messages 96,97,98,99)

CHECK VALIDATION PRINTING (Top, Form must be positioned Down and far Right)

Printer Driver: ITH90RCT.PRD
Select Rcpt Printing: 27,102 (ITH90RCT.PRD Setup String)
Select Top Validation: 27,106,3 (Code 13 On)
Eject Slip 27,107 (Code 12 On)
Form Files: ITHVALIT.NVC (Prints Date, Nvc#, Amount,
Form Messages 96,97,98,99)
Form is rotated 180 degrees so checks can be inserted top-down.

SLIP/RECEIPT PRINTING (Front, Form must be positioned far Right)

Printer Driver: ITH90RCT.PRD
Select Rcpt Printing: 27,102 (ITH90RCT.PRD Setup String)
Select Slip Printing: 27,105 (Code 11 On)
Eject Slip 27,107 (Code 12 On)
Form Files: ITHSLIP.NVC (Modified Receipt: Starallf.nvc)

MICR READER

Read & Return Data: 27,109,82 (Wasn't able to have EDC work w/ MICR).

LABEL PRINTING

Printer Driver: ITH90LBL.PRD
Com Parameters: 9600,N,8,1,LF
DOS Command: None
Form File(s): 1WIDE.PTG, MAIL1.LBL, SHIP1.LBL (& other non Barcode labels)
Barcode File(s): ITH90128.PTG.PTG (1x3 inch, Code 128 w/ Product Code Barcoded)
ITH9039.PTG.PTG (1x3 inch, Code 3 of 9 w/ Product Code Barcoded)
ITH90ST.PTG.PTG (1x3 inch, Code 128 w/ Stock Number Barcoded)
ITH90UPC.PTG.PTG (1x3 inch, UPC-A, must be 12 characters that include a check digit. Printer will print a check digit & will not match inv).

