

Keystroke™

Point Of Sale

Ithaca Series 80 Printers

.....

PRINTER INFORMATION

Ithaca Model: 82-S-AC
Ithaca Part Number: SRB-11457-002
Ithaca Serial Number: JC001975213
Programmer Manual: Ithaca P/N: 100-9645 Rev A 10/14/97
Receipt Paper: 3.10" (Manual reads 3.15")
Ithaca P/N: 100-9109
Label Stock: None Supplied:
Tried: 3.15 Star Micronics Thermal Label(Label size 3.15" x 1.00")
Interface: Serial 9F-9F, Ithaca Cable P/N 10-2020 (Supplied)
or Serial 9F-25F, Ithaca Cable P/N 10-2021
4-(6/1),(6/1)-4,3-2,2-3,5-5,7-8,8-7
Power Supply: Custom Power Supply, Ithaca P/N BPA-601-24-1984
(100-240V-2A, + 24V-2.5A)

Keystroke POS Setup Information

RECEIPT PRINTING (Epson TM-T8x Emulation)

Printer Driver: ITHACA80.PRD
Com Parameters: 9600,N,8,1,LF
DOS Command: None
Form Files: STAR.NVC (Or any STAR*.NVC form)
Cut Command: 27,105

CASH DRAWER (Epson TM-T8x Emulation)

Drawer Open Codes: 27,112,48,50*,250 (Not tested)
*Note: Do Not use 25(Cut Command)
Drawer Status Codes: 27,117,48 BitMask=0 (Not tested)

LABEL PRINTING:

Printer Driver: ITHACA80.PRD
Com Parameters: 9600,N,8,1,LF
DOS Command: None
Form File(s): 1WIDE.PTG, MAIL1.LBL, SHIP1.LBL (& other non Barcode labels)
Barcode File(s): ITHC39PC.PTG.PTG (1x3 inch, w/ Product Code Barcoded)
ITHC39ST.PTG.PTG (1x3 inch, w/ Stock Number Barcoded)
ITHUPCPC.PTG.PTG (1x1 inch, UPC-A, must be 12 characters
that include a check digit, 11 characters will print a check digit and
will not match inv.)